Issued: 20th September 2023



## DECLARATION OF PERFORMANCE in accordance with Annex III of Regulation (EU) No 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No 574/2014

No. 60401

Unique identification code of the product type: 60401 ARDEX WA Epoxy adhesive, EN 12004:R2T

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

## Improved reaction resin adhesive with reduced slip for internal and external tiling

Name, registered trade name or registered trade mark and contact address of the manufacturer:

ARDEX GmbH Friedrich-Ebert-Str. 45 58453 Witten Germany

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3
Reaction to fire: System 4

Harmonised standard:

EN 12004:2007+A1:2012

Notified body:

LGAI TECHNOLOGICAL CENTER, S. A./Applus, identification number 0370

Issued: 20th September 2023

## Declared Performance:

Essential Characteristics	Performance	System for assessing and reviewing performance consistency	Harmonised Technical Specification		
Fire class:	E	System 4	EN 12004:2007+A1:2012		
Bond strength					
Initial shear adhesion strength:	≥ 2.0 N/mm²	System 3	EN 12004:2007+A1:2012		
Durability of bond strength					
Shear adhesion strength after thermal shock:	≥ 2.0 N/mm²	System 3	EN 12004:2007+A1:2012		
Shear adhesion strength after water immersion:	≥ 2.0 N/mm²	System 3	EN 12004:2007+A1:2012		
Release of dangerous substances:	NPD				

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

	DEX Gmbi	-
	∋drich-Ebert-Str	. 45
OL/	3453 Witt	en

Arnd Haase R & D Deputy Director Dr. Robert Schulte Holthausen

R & D Section Head

Witten, 20th September 2023

(Place and date of issue)

## **Additional Product Characteristics**

Additional Characteristics  Performance					
Slip:	≤ 0.5 mm	System 3	EN 12004:2007+A1:2012		