



**DECLARATION OF PERFORMANCE**  
**in accordance with Annex III of Regulation (EU) No 305/2011**  
**(Construction Product Regulation)**  
**amended by Commission Delegated Regulation (EU) No 574/2014**  
**No 54062**

Unique identification code of the product type: **54062 ARDEX X 77 S, EN 12004:C2FTE-S1**

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Improved fast setting deformable cementitious adhesive  
with reduced slip and extended open time for internal and  
external tiling**

Name, registered trade name or registered trade mark and contact address of the manufacturer:

**ARDEX Skandinavia A/S**  
**Marielundvej 4**  
**2730 Herlev**  
**Denmark**

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**  
**Reaction to fire: System 4**

Harmonised standard: **EN 12004:2007+A1:2012**

Notified body:



**MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN (MPA NRW)** Identification number  
**0432**

Declared Performance:

Essential Characteristics	Performance	System for assessing and reviewing performance consistency	Harmonised Technical Specification
Reaction to fire:	E	System 4	EN 12004:2007+A1:2012
<b>Bond strength</b>			
Initial tensile adhesion strength:	$\geq 1.0 \text{ N/mm}^2$	System 3	EN 12004:2007+A1:2012
Early tensile adhesion strength after 6 hours:	$\geq 0.5 \text{ N/mm}^2$	System 3	EN 12004:2007+A1:2012
<b>Durability of bond strength</b>			
Tensile adhesion strength after heat ageing:	$\geq 1.0 \text{ N/mm}^2$	System 3	EN 12004:2007+A1:2012
Tensile adhesion strength after water immersion:	$\geq 1.0 \text{ N/mm}^2$	System 3	EN 12004:2007+A1:2012
Tensile adhesion strength after freeze-thaw cycles:	$\geq 1.0 \text{ N/mm}^2$	System 3	EN 12004:2007+A1:2012
Release of dangerous substances:	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


  
**ARDEX GmbH**  
 Friedrich-Ebert-Str. 45  
 58453 Witten

Dr. Jörg W. Sieksmeier  
R & D Director

Dr. Robert Schulte Holthausen  
R & D Section Head

Witten, 5<sup>th</sup> July 2023

(Place and date of issue)

**Additional Product Characteristics**

Additional Characteristics	Performance	System for assessing and reviewing performance consistency	Harmonised Technical Specification
<b>Special Characteristics</b>			
Open time:	$\geq 0.5 \text{ N/mm}^2$ after not less than 30 minutes	System 3	EN 12004:2007+A1:2012
Slip:	$\leq 0.5 \text{ mm}$	System 3	EN 12004:2007+A1:2012
Transverse deformation:	$\geq 2.5 \text{ mm}$ and $< 5 \text{ mm}$	System 3	EN 12004:2007+A1:2012