

Sustainability data sheet

ARDEX E 90

Artificial Resin Modification

Artificial resin modification for ARDEX X 7G FLEX, ARDEX X 77W, ARDEX X 77, ARDEX X 78, ARDEX X 77S, ARDEX X 78S, ARDEX S 21, ARDEX S 28 NEU, ARDEX N 23, ARDEX N23 W.

Emissions

According GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf) -

According Emission Classification of Building Materials -

solvent-free

EPD (Environmental Product Declaration)

ARDEX E 90 corresponds to FEICA EPD:

EPD-FEI-20160084-IBG1-EN

According BASTA

ARDEX E 90 is BASTA registered.

BASTA registration means that we can verify that this product meets agreed properties criteria regarding properties hazardous to the environment and health. See www.bastaonline.se



Technical Assessment

According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):

GISCODE D1 – solvent-free

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



ARDEX E 90

Artificial Resin Modification

Sustainable Building

According DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen)

Version 2018

DGNB criteria ENV 1.2: Local environmental impact

ARDEX E 90 can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX E 90 has the GISCODE D1.

ARDEX E 90 fulfills the requirements for Quality Level 1.

Version 2015

DGNB criteria ENV 1.2: Local environmental impact

ARDEX E 90 can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX E 90 has the GISCODE D1.

ARDEX E 90 fulfills the requirements for Quality Level 1.

Sustainable Building

According LEED (Leadership in Energy and Environmental Design)

Version 4 (2014)

EQ: Low Emitting Materials

ARDEX E 90 does not meet the requirements according EMICODE® based on GEV which are accepted by LEED.

ARDEX E 90 does not meet the requirements.

MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX E 90 corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

ARDEX E 90 fulfills the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.

Version 2009

IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

The permitted limit value in the category primers, sealings and undercoatings according SCAQMD Rule 1168 is 65 g/L. The VOC value of ARDEX E 90 according SCAQMD Rule 1168 is < 65 g/L.

ARDEX E 90 meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.

MR Credit 5.1 und 5.2: Regional Materials

Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



ARDEX E 90

Artificial Resin Modification

According BREEAM-NOR (Building Research Establishment Environmental Assessment Methodology)

Version 2016

BREEAM-NOR criteria Hea 02 Indoor air quality

ARDEX E 90 does not fulfill the required emission limits.

ARDEX E 90 does not meet the requirements according BREEAM-NOR.

According Nordic Swan Ecolabelling

ARDEX E 90 is listed in the database for building products that can be used in Nordic Swan Ecolabelled buildings.

Notice: This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship. Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH
Witten, 10/01/2019

ARDEX GmbH
Friedrich-Ebert-Straße 45
58453 Witten
www.ardex.de

Tel.: +49 2302 664-511
Fax: +49 2302 664-298
kundendienst@ardex.de
www.ardex.de

