Sustainability data sheet

ARDEX K 15 Levelling and Smoothing Compound

Filling and repairing of cement sreeds, calcium sulfate screeds, mastic asphalt, magnesite screeds, concrete floors and other subfloors.

A+

EMICODE[®] EC 1 R,

very low emission

Emissions

According GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf)

According French VOC Classification

solvent-free

EPD (Environmental Product Declaration)

ARDEX K 15 corresponds to FEICA EPD:

EPD-FEI-20160017-IBG1-EN

EMICO

BASTA

According BASTA

ARDEX K 15 is BASTA registered.

BASTA registration means that we can verify that this product meets agreed properties criteria regarding properties hazardous to the environment and health. See www.bastaonline.se

Technical Assessment

According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe): GISCODE ZP1 - cementitious product, low-chromate ARDEX GmbH Friedrich-Ebert-Straße 45 58453 Witten www.ardex.de

Tel.: +49 2302 664-511 Fax: +49 2302 664-298 kundendienst@ardex.de www.ardex.de



Sustainable Building

According DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen)

Version 2018

DGNB criteria ENV 1.2: Local environmental impact

ARDEX K 15 can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX K 15 has the GISOCDE ZP1 and is certified by EMICODE[®] EC 1 R, very low emission, based on GEV.

ARDEX K 15 fulfills the requirements for highest Quality Level 4.

Version 2015 DGNB criteria ENV 1.2: Local environmental impact ARDEX K 15 can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper). ARDEX K 15 is certified by EMICODE[®] EC 1 R, very low emission, based on GEV.

ARDEX K 15 fulfills the requirements for highest Quality Level 4.

According LEED (Leadership in Energy and Environmental Design)

Version 4 (2014)

EQ: Low Emitting Materials

ARDEX K 15 meets the requirements according EMICODE[®] EC 1 R, very low emission, based on GEV which are accepted by LEED.

ARDEX K 15 meets the requirements and contributes to achieving one LEED point under EQ: Low Emitting Materials.

MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX K 15 corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) "cradle to gate".

ARDEX K 15 fulfills the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.

Version 2009

IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants Cement based filling compound are not directly described by LEED. But the permitted limit value in the category coatings is 50 g/L. The VOC value of ARDEX K 15 is < 50 g/L.

ARDEX K 15 meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.

MR Credit 5.1 und 5.2: Regional Materials Production site: 58453 Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

ARDEX GmbH Friedrich-Ebert-Straße 45 58453 Witten www.ardex.de

Tel.: +49 2302 664-511 Fax: +49 2302 664-298 kundendienst@ardex.de www.ardex.de



Sustainable Building

According BREEAM-NOR (Building Research Establishment Environmental Assessment Methodology)

Version 2016

BREEAM-NOR criteria Hea 02 Indoor air quality

ARDEX K 15 fulfills the required emission limits and is certified by EMICODE[®] EC 1 R, very low emission, based on GEV which is accepted as documentation.

ARDEX K 15 meets the requirements according BREEAM-NOR and contributes to achieving one credit under Hea 02 Indoor air quality.

According BREEAM (Building Research Establishment Environmental Assessment Methodology)

Version 2016

BREEAM criteria Hea 02 Indoor air quality

ARDEX K 15 can be classified as Flooring materials (including floor levelling compounds and resin flooring). ARDEX K 15 meets the requirements according Table 17: Emission criteria by product type and Table 18: Exemplary level emission criteria by product type.

ARDEX K 15 is certified by EMICODE® EC 1 R, very low emission, based on GEV.

ARDEX K 15 meets the requirements according BREEAM and contributes to achieving one credit under Hea 02 Indoor air quality.

According Nordic Swan Ecolabelling

ARDEX K 15 is listed in the database for building products that can be used in Nordic Swan Ecolabelled buildings.

Notice: This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship.

Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH Witten, 11/01/2019 ARDEX GmbH Friedrich-Ebert-Straße 45 58453 Witten www.ardex.de

Tel.: +49 2302 664-511 Fax: +49 2302 664-298 kundendienst@ardex.de

www.ardex.de

