

# Sustainability data sheet

## ARDEX X 701 FW

### Flexible Tile Adhesive

used for installing ceramic tiles and stoneware, especially fine stoneware tiles and glass and porcelain mosaics. In- and outdoors.

#### Emissions

According GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf)

**EMICODE® EC 1<sup>PLUS</sup>**,  
very low emission



solvent-free

#### EPD (Environmental Product Declaration)

ARDEX X 701 FW corresponds to FEICA EPD:

**EPD-DBC-20220218-IBF1-EN**

#### According BASTA

ARDEX X 701 FW is not BASTA registered.

BASTA registration means that we can verify that this product meets agreed properties criteria regarding properties hazardous to the environment and health. See [www.bastaonline.se](http://www.bastaonline.se)

## Technical Assessment

#### Meets the C2 requirements according to EN 12004

C2 TE, Cement mortar for increased requirements with additional characteristic values extended open time (E) and reduced slipping (T).

#### Meets the S1 requirements according to EN 12002

S1 deformability > 2,5 mm

**According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):**  
**GISCODE ZP1** - cementitious product, low-chromate

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

[kundendienst@ardex.de](mailto:kundendienst@ardex.de)

[www.ardex.de](http://www.ardex.de)

## Sustainable Building

**According DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen)**



# ARDEX X 701 FW

Flexible Tile Adhesive

---

## Version 2018

### DGNB criteria ENV 1.2: Local environmental impact

ARDEX X 701 FW can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (e.g. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX X 701 FW has the GISCODE ZP1 and is certified by EMICODE® EC 1<sup>PLUS</sup>, very low emission, based on GEV.

**ARDEX X 701 FW fulfils the requirements for highest Quality Level 4.**

## Version 2015

### DGNB criteria ENV 1.2: Local environmental impact

ARDEX X 701 FW can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (e.g. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX X 701 FW is certified by EMICODE® EC 1<sup>PLUS</sup>, very low emission, based on GEV.

**ARDEX X 701 FW fulfils the requirements for highest Quality Level 4.**

---

## According LEED (Leadership in Energy and Environmental Design)

### Version 4 (2014)

#### EQ: Low Emitting Materials

ARDEX X 701 FW meets the requirements according EMICODE® EC 1<sup>PLUS</sup>, very low emission, based on GEV which are accepted by LEED.

**ARDEX X 701 FW meets the requirements and contributes to achieving one LEED point under EQ: Low Emitting Materials.**

#### MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX X 701 FW corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate “.

**ARDEX X 701 FW fulfils the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.**

### Version 2009

#### IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

The permitted limit value in the category primers, sealings and undercoatings according SCAQMD Rule 1168 is 65 g/L. The VOC value of ARDEX X 701 FW according SCAQMD Rule 1168 is < 65 g/L.

**ARDEX X 701 FW meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.**

#### MR Credit 5.1 und 5.2: Regional Materials

##### Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometres) can be contributed to achieving one LEED point.

---

ARDEX GmbH  
Friedrich-Ebert-Straße 45  
58453 Witten  
[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511  
Fax: +49 2302 664-298  
[kundendienst@ardex.de](mailto:kundendienst@ardex.de)  
[www.ardex.de](http://www.ardex.de)

**Sustainable Building**



# ARDEX X 701 FW

Flexible Tile Adhesive

**According BREEAM-NOR** (Building Research Establishment Environmental Assessment Methodology)

**Version 2016**

**BREEAM-NOR criteria Hea 02 Indoor air quality**

ARDEX X 701 FW fulfils the required emission limits and is certified by EMICODE® EC 1<sup>PLUS</sup>, very low emission, based on GEV which is accepted as documentation.

**ARDEX X 701 FW meets the requirements according BREEAM-NOR and contributes to achieving one credit under Hea 02 Indoor air quality.**

**According BREEAM** (Building Research Establishment Environmental Assessment Methodology)

**Version 2016**

**BREEAM criteria Hea 02 Indoor air quality**

ARDEX X 701 FW can be classified as Interior adhesives and sealants (including flooring adhesives). ARDEX X 701 FW meets the requirements according Table 17: Emission criteria by product type and Table 18: Exemplary level emission criteria by product type.

ARDEX X 701 FW is certified by EMICODE® EC 1<sup>PLUS</sup> very low emission, based on GEV.

**ARDEX X 701 FW meets the requirements according BREEAM and contributes to achieving one credit under Hea 02 Indoor air quality.**

**According Nordic Swan Ecolabelling**

**ARDEX X 701 FW is listed in the database for building products that can be used in Nordic Swan Ecolabelled buildings.**

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de

**Notice:** This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification



# ARDEX X 701 FW

## Flexible Tile Adhesive

criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship.  
Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH  
Witten, 27/02/2023

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

[kundendienst@ardex.de](mailto:kundendienst@ardex.de)

[www.ardex.de](http://www.ardex.de)

